

Skid Mounted Spray Packages for De-icing and Dust Control

No metal wetted parts, Industrial Gas Engine. 12volt on/off spray control std. Self loading, Bypass control, DOT reflective markers, Economical.In cab control.Includes spray bar with quick coupled spray tips, Reese Style, Spray Bar Mount or Adjustable Height Kit for larger trucks.

PICTURE COMING SOON

200 GALLON SKIDDED SPRAYER

- 47" WIDE x 6'-1" LONG; 2400# WET WEIGHT
- MAINTENANCE FREE ALL POLY SKID WITH STAINLESS STEEL FASTENERS
- 200 GALLON LOW PROFILE HIGH DENSITY POLYETHYLENE TANK
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 66" x 1-1/2" SPRAY BAR WITH 5 NOZZLE PORTS & 5 INSTALLED FLAT FAN NOZZLES; 10' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH
- SPECIAL UPWARD DISCHARGE PORTS FOR OVER THE TAILGATE USE
- SPECIAL FOR THE SHORT BOX PICK-UP TRUCKS

230 GALLON SKIDDED SPRAYER

- 44" WIDE x 6'-4" LONG; 2600# WET WEIGHT
- MAINTENANCE FREE ALL POLY SKID WITH STAINLESS STEEL FASTENERS
- 230 GALLON HIGH DENSITY POLYETHYLENE TANK
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 1-1/2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH



300 GALLON SKIDDED SPRAYER

- 44" WIDE x 8'-2" LONG; 3700# WET WEIGHT
- MAINTENANCE FREE ALL POLY SKID WITH STAINLESS STEEL FASTENERS
- 300 GALLON HIGH DENSITY POLYETHYLENE TANK
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 66" x 1-1/2" SPRAY BAR WITH 9 NOZZLE PORTS & 5 INSTALLED FLAT FAN NOZZLES; 10' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

525 GALLON SKIDDED SPRAYER

- 54" WIDE x 8'-4" LONG; 6100# WET WEIGHT
- MAINTENANCE FREE ALL POLY SKID WITH STAINLESS STEEL FASTENERS
- 525 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 5 YR WARRANTY & 2 HOOP SET
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 1-1/2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH
- THIS UNIT WILL NOT FIT IN STANDARD PICK-UP TRUCKS DUE TO WIDTH & WEIGHT (WILL FIT IN HEAVY DUTY LARGER TRUCKS)

