

Skid Mounted Spray Packages for De-icing and Dust Control

No metal wetted parts, Industrial Gas Engine. 12volt on/off spray control std. Self loading, Bypass control, DOT reflective markers, Economical. In cab control. Includes spray bar with quick coupled spray tips, Reese Style, Spray Bar Mount or Adjustable Height Kit for larger trucks.



735 GALLON SKIDDED SPRAYER

- 54" WIDE x 10'-7" LONG; 8400# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 735 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 1-1/2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

935 GALLON SKIDDED SPRAYER

- 68" WIDE x 8'-9" LONG; 11000 # WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 935 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH



1035 GALLON SKIDDED SPRAYER

- 84" WIDE x 9'-6" LONG; 12100# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 1035 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

1300 GALLON SKIDDED SPRAYER

- 68" WIDE x 11'-6" LONG; 15000# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 1300 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

