

Skid Mounted Spray Packages for De-icing and Dust Control

No metal wetted parts, Industrial Gas Engine. 12volt on/off spray control std. Self loading, Bypass control, DOT reflective markers, Economical. In cab control. Includes spray bar with quick coupled spray tips, Reese Style, Spray Bar Mount or Adjustable Height Kit for larger trucks.



1650 GALLON SKIDDED SPRAYER

- 77" WIDE x 13'-8" LONG; 20000# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 1650 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

2000 GALLON SKIDDED SPRAYER

- 66" WIDE x 15'-5" LONG; 24000# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 2000 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

PICTURE COMING SOON

PICTURE COMING SOON

2600 GALLON SKIDDED SPRAYER

- 88" WIDE x 14'-11" LONG; 31000 # WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 2600 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

PICTURE COMING SOON

3000 GALLON SKIDDED SPRAYER

- 98" WIDE x 14'-0" LONG; 35000# WET WEIGHT
- PRESSURE TREATED SKID WITH STAINLESS STEEL FASTENERS
- 3000 GALLON HIGH DENSITY POLYETHYLENE TANK W/ 3 HOOP SET
- MAINTENANCE FREE HEAVY DUTY POLY EQUIPMENT PLATFORM
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1-1/2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES & 4 INSTALLED PLUGS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH