

Skid Mounted Spray Packages for De-icing and Dust Control

No metal wetted parts, Industrial Gas Engine. 12volt on/off spray control std. Self loading, Bypass control, DOT reflective markers, Economical. In cab control. Includes spray bar with quick coupled spray tips, Reese Style, Spray Bar Mount or Adjustable Height Kit for larger trucks.



1" EQUIPMENT PLATFORM

- 66" WIDE x 24" LONG;
- MAINTENANCE FREE HEAVY DUTY POLY PLATFORM WITH STEEL FRAME
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 1" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- BASIC FITTINGS INCLUDED FOR CONNECTION TO TANK
- 90" x 1-1/2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES, 4 INSTALLED PLUGS & 9 DRILL TIPS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- REESE HITCH ADAPTOR
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH

2" EQUIPMENT PLATFORM

- 66" WIDE x 24" LONG;
- MAINTENANCE FREE HEAVY DUTY POLY PLATFORM WITH STEEL FRAME
- 5.5 HP INDUSTRIAL GAS HONDA ENGINE W/ LOW OIL ALERT
- 2" 180 GPM, 45 PSI POLY SELF-PRIMING PUMP
- 1 PLACE 12 VOLT 2" ELECTRIC VALVE
- 1 PLACE 1" MANUAL ON/OFF VALVE
- BASIC FITTINGS INCLUDED FOR CONNECTION TO TANK
- 90" x 2" SPRAY BAR WITH 9 NOZZLE PORTS, 5 INSTALLED FLAT FAN NOZZLES, 4 INSTALLED PLUGS & 9 DRILL TIPS; 14' PATH, 10 TO 60 GALLONS PER LANE MILE @ 30 MPH RATE
- REESE HITCH ADAPTOR
- 12 VOLT ON/OFF CONTROLLER, WITH CAB MOUNTED SWITCH



Spray Bars

66" wide for 10 foot spray path. Use for pickup truck.

90" wide 14 foot path, 1 1/2" PVC with 9 ports & 5 installed Quick coupled nozzles for even distribution of de-icer, change nozzle for different capacities

FOR FULL LINE OF SPRAY BARS PLEASE SEE PAGES 109 & 110

**Other Size Skids & Platforms Available
Please call**