

# MICRO TRAK CONTROLS

The MT-2405F II offers 5 Boom Control that provides the target application rate in one display, the second display allows the option to select between several monitored display functions: speed, distance, tank level, flow rate per minute and area per hour plus 3 separate gallon counters and acre counters with independent resets.

## NEW FEATURES!

- Designed for use with existing boom control switches
- Custom harness kits available to update manual sprayer control systems

## STANDARD FEATURES

- On-the-go rate adjustment
- New dual display readout provides uninterrupted application rate numbers
- Heavy-duty console with built-in boom controls for up to 5 separate boom sections
- Flash memory for simple customization
- Built-in capability for future VRA
- Records area and volume in 3 independent counters so individual jobs can be tracked
- Tank counter shows amount remaining in tank
- Enhanced reliability, precision and accuracy
- Push-button auto/manual feature for spot treatments
- Minimum flow feature to ensure proper application pattern as ground speed slows to extremes
- Precise rate control regardless of field conditions
- Flow based control
- Controls electric and hydraulic valves/motors



PART NUMBER	DESCRIPTION
01226	MT-2405F SPRAY CONSOL

The RoadMaster is an electronic control system that can help you operate more cost-effectively by providing the information you need to **maintain proper application rates of liquid de-icer, anti-icing chemicals, and dust control.**

## **BEST SELLER**



- Four Operating Modes
- Built-in VRA/AVL Communications
- Extensive Downloadable Data List
- Keylock Switch
- Built-in Alarm Messages

PART NUMBER	DESCRIPTION
01590	ROADMASTER

The Astro GPS Speed Sensors are a direct replacement for magnetic wheel speed sensors or radar guns and can interface to most brands of monitors and controllers.

The magnetic mount bracket is standard and allows for quick installation and easy transfer from one vehicle to another. Optional mount kits are available.

Not affected by crop canopies or adverse ground conditions. Improve productivity and efficiency!



PART NUMBER	DESCRIPTION
01425	ASTRO 5 GPS SPEED SENSOR

## MICRO-TRAK 2" Flanged Flow Meter

- Glass-filled nylon
- Rating: 10 to 100 GPM (38 to 380 lpm)
- 175 PSI (13-bar) max



PART NUMBER	DESCRIPTION
01514	2" FLANGED FLOW METER

## MICRO-TRAK 1-1/2" Flanged Servo Valve

- Glass-filled nylon
- 150 PSI (10-bar) max



PART NUMBER	DESCRIPTION
17140	1-1/2" FLANGED SERVO VALVE