

HOSE / TUBING

ALL HOSE CAN BE CUT TO YOUR SPECIFIC LENGTH

PVC SUCTION HOSE – STYLE K (CLEAR)



PART NUMBER	I.D. x O.D.	LENGTH	M.B.R.	W.P.	WT. EA.
12013590	¾" x 1.00"	100'	2.0"	100#	20#
12015003	1" x 1.25"	100'	3.0"	90#	26#
12016506	1-1/4" x 1.515"	100'	4.0"	70#	32#
12017006	1-1/2" x 1.81"	100'	5.0"	70#	45#
12017502	2" x 2.34"	100'	7.0"	60#	63#
12017515	3" x 3.42"	100'	10.0"	50#	116#

Applications: A PVC suction / discharge hose for water, light chemicals, and pumping service in the agricultural, rental, construction, marine, and irrigation industries.

Construction: A smooth bore hose made of flexible abrasion resistant extruded clear PVC with a rigid PVC helix.

Temperature Range: -10°F to 130°F (under static conditions)

W.P. and M.B.R. (continuous service): Applicable @ 68°F

Assemblies available upon request.

EPDM RUBBER WITH POLYETHYLENE HELIX (YELLOW)



PART NUMBER	I.D. x O.D.	LENGTH	VAC. RATE	M.B.R.	W.P.	WT. EA.
12012795	1" x 1.34"	100'	28 in/HG	4.0"	80#	23#
12012797	1-1/4" x 1.61"	100'	28 in/HG	5.0"	70#	30#
12012800	1-1/2" x 1.96"	100'	28 in/HG	6.0"	60#	47#
12012805	2" x 2.49"	100'	28 in/HG	9.0"	60#	69#
12012810	3" x 3.60"	100'	28 in/HG	12.0"	50#	119#
12012815	4" x 4.69"	100'	28 in/HG	17.0"	45#	181#

Applications: A lightweight, rugged, flexible suction / discharge hose for the agricultural, rental, mining, and construction industries. Hose is resistant to herbicides and pesticides, including Lasso and has good flexibility even in cold weather.

Construction: EPDM with polyethylene helix reinforcement that serves as a scuff strip.

Temperature Range: -30°F to 140°F.

W.P., M.B.R., and Vac. Rating: Applicable @ 68°F.

Assemblies available upon request.

WARNING: Not for transfer of anhydrous ammonia. For undiluted chemicals, please call for hose recommendations.

ENFORCER- REINFORCED SUCTION/DISCHARGE HOSE (BLACK)



PART NUMBER	I.D. x O.D.	LENGTH	VAC. RATE	M.B.R.	W.P.	WT. EA.
12012960	1-1/4" x 1.60"	100'	29.8 in/HG	3.0"	100#	34#
12012962	1-1/2" x 1.87"	100'	29.8 in/HG	3.0"	100#	47#
12012964	2" x 2.66"	100'	29.8 in/HG	5.5"	100#	87#
12012966	3" x 3.86"	100'	29.8 in/HG	7.0"	85#	205#

Applications: A reinforced, flexible suction / discharge hose for the agricultural and construction industries. Hose is resistant to diluted herbicides and pesticides with good flexibility in sub-zero weather.

Construction: EPDM tube with polyethylene helix and a high tensile fabric reinforcement.

Temperature Range: -30°F to 140°F.

W.P., M.B.R., and Vac. Rating: Applicable @ 72°F.

Assemblies available upon request.

WARNING: Not for transfer of anhydrous ammonia. For undiluted chemicals, please call for hose recommendations.