

# HOSE CLAMPS

## FEATURES

- Total stainless steel construction makes these clamps extra tough and durable.
- Idea for use in corrosive environments and applications such as plumbing, sprinkler systems, swimming pools, automotive, marine and agricultural environments.



PART NUMBER	DESCRIPTION	MIN/MAX DIAMETER
236302	3/8" WORM SCREW CLAMP (5/16" BAND) SAE 4	0.2188"/0.625"
236402	1/2" WORM SCREW CLAMP (5/16" BAND) SAE 6	0.4375"/0.7813"
236702	3/4" WORM SCREW CLAMP (1/2" BAND) SAE 10	0.5625"/1.0625"
236902	1" WORM SCREW CLAMP (1/2" BAND) SAE 16	0.8125/1.50"

## FEATURES

- Perfect for tight, hard to reach spaces!
- Minimizes parts that protrude by tightening together versus tightening away from.
- Deep socket tools not required.
- 300 Stainless steel construction.



PART NUMBER	DESCRIPTION	MIN/MAX DIAMETER	MAX TORQUE
BC114	1" 300 SS FLOATING BRIDGE WITH LOCKWASHER	1.14"/1.22"	75 IN-LBS

## FEATURES

- Stainless steel construction.
- Stainless steel bolt with silver plated nut to prevent seizing.
- 360° sealing surface.
- Ideal for high torque applications.
- Nylon lock nut feature.
- Strong, positive connections where ordinary hose clamps fail.
- T-bolt design.
- 3 spot welds for extra strength.



PART NUMBER	DESCRIPTION	MIN/MAX DIAMETER	MAX TORQUE
TC120	1" T-BOLT HOSE CLAM	1.20"/1.34"	75 IN-LBS
TC130	1-1/4" T-BOLT HOSE CLAM	1.30"/1.70"	75 IN-LBS
TC162	1-1/4" T-BOLT HOSE CLAM	1.62"/1.87"	125 IN-LBS
TC181	1-1/2" T-BOLT HOSE CLAM	1.81"/2.06"	125 IN-LBS
TC218	2" T-BOLT HOSE CLAM	2.18"/2.50"	125 IN-LBS
TC231	2" T-BOLT HOSE CLAM	2.31"/2.62"	125 IN-LBS
TC331	3" T-BOLT HOSE CLAM	3.31"/3.62"	125 IN-LBS
TC343	3" T-BOLT HOSE CLAM	3.43"/3.75"	125 IN-LBS
TC456	4" T-BOLT HOSE CLAM	4.56"/4.94"	125 IN-LBS

# HOSE KITS

